

SRT1 RED SURFACE BACKBOX



A surface mounted back box for the HCP-E(SCI) manual call point which is 32 mm deep.

PART. NO

MUS041W

FEATURES

- Durable
- For use with HCP-E call point range
- Allows addressable call point to be surface mounted

INTELLIGENT OUTDOOR MANUAL CALL POINT GLASS, ISOLATED



The IP67 Honeywell Morley-IAS addressable call point is used in humidity environments to provide a safe and reliable device in areas with dust or humidity.

The IP67 addressable MCP is provided with IP67 surface mounting enclosure and transparent cover.

PART. NO

W5A-RP06SG-K013-41

FEATURES

- Includes transparent cover PS200 and surface mounting enclosure IP67

TECHNICAL SPECIFICATION

OPERATING VOLTAGE	15 ... 30 V DC	TEMPERATURE RANGE	-30°C ... 70°C
DIMENSIONS (HXWXD)	H: 97.5 mm W: 105 mm D: 75.5 (surface mounted & transparent cover)	MAX. WIRE GAUGE	2.5 sqmm
WEIGHT	350g	MATERIAL	ABS plastic
COLOR	Red	QUIESCENT CURRENT	260 uA @ 24 V DC (w/o isolator) 360 uA @ 24 V DC (with isolator)
INGRESS PROTECTION	IP67	ALARM CURRENT	6 mA @ 24 V DC
RELATIVE HUMIDITY	0 ... 95% (non-condensing)		